

## Safety Data Sheet

### Section 1. Identification

**Product name** : BriteGuard™ TRIDIP 105  
**Product code** : 424758  
**Uses advised against** : Consumer, private households, general public  
**Product type** : Liquid.  
**Validation date** : 1/23/2014.

Manufacturer - Supplier	Telephone no.:	Fax no.	Emergency phone:
Enthone Inc 350 Frontage Road West Haven, CT 06516	Tel: (203) 934-8611	Fax:(203) 799-8179	DOMESTIC NORTH AMERICA 800-424-9300 INTERNATIONAL, CALL +1 703-527-3887 (collect calls accepted)
Cookson Enthone Chemistry Trading (Shanghai) Co., Ltd. Rm 201, No.388 of Muhua North Road, Fengxian District, Shanghai	Tel: 86-21-6390 0600	Fax: 86-21-50912810	Tel: 0532-8388 9090 (24- hour)
Enthone Chemistry A Division of Cookson Singapore Pte Ltd 26 Tuas West Road Singapore 638382	Tel: (65) 6861 1773	Fax: (65) 68611145	Tel: (65) 6861 1773
ENTHONE SDN. BHD. Lot 34 & 36 Lorong IKS Juru 7 Taman Perindustrian Ringan Juru 14100 Simpang Ampat Seberang Perai Selatan Penang, Malaysia	Tel: 60 - 4 507 7787	Fax: 60 4 507 0621	Tel: 60 4 507 7787
Enthone Korea 1Ra 310, Sihwa Industrial Complex, 1247-9, Jungwang-Dong, Siheung-Si, Gyeonggi-Do, Korea	Tel: 82-31-432-4100	82-31-433-1478	Tel: 82-31-432-4100
Enthone Inc. Taiwan Branch 2F, B Building, No. 10, Lu-Shing Street, Luchu Hsiang, 338 Taoyuan, Taiwan	Tel: 03-312-0280	Fax: 03-312-0380	Tel: 886-937408981
Alent Japan Company - Enthone 480-28 Higashitoyoda, Hiratsuka, Kanagawa 254-0082, Japan	Tel: 81-463-51-4330	Fax: 81-463-55-2588	Tel: 81-(0)463-51-4330
Enthone India A Division of Cookson India Pte. Ltd Developed Plot no 16, North Phase, SIDCO Industrial estate, Ambattur, Chennai - 600098.	Tel: 91-44-26252666	Fax: 91-44-26258627	Tel: 91-44-26252666

### Section 2. Hazards identification

**Classification of the substance or mixture** : OXIDIZING LIQUIDS - Category 2  
 ACUTE TOXICITY: INHALATION - Category 1  
 SKIN CORROSION/IRRITATION - Category 1A  
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 AQUATIC TOXICITY (ACUTE) - Category 1

#### GHS label elements

Continued on next page

## Section 2. Hazards identification

Symbol :



Signal word :

Danger

Hazard statements :

May intensify fire; oxidizer.  
Fatal if inhaled.  
Causes severe skin burns and eye damage.  
Very toxic to aquatic life.

Precautionary statements

Prevention :

Read label before use. Do not breathe dust or mist. Wash thoroughly after handling. Wear protective gloves. Wear protective clothing. Wear eye/face protection. Wear respiratory protection. Keep away from heat. Take any precaution to avoid mixing with incompatibles. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Keep out of reach of children. Do not breathe vapor. If medical advice is needed, have product container or label at hand.

Response :

Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Collect spillage.

Storage :

Store locked up. Store away from combustibles.

Disposal :

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification : Not available.

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Inorganic acid 1	50-60	-
Chromium III Salt	20-30	-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

Inhalation :

Get medical attention immediately. If it is suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Move exposed person to fresh air. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Keep person warm and at rest. If unconscious, place in recovery position and get medical attention immediately. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Continued on next page

## Section 4. First aid measures

- Ingestion** : Get medical attention immediately. Chemical burns must be treated promptly by a physician. Move exposed person to fresh air. Wash out mouth with water. Keep person warm and at rest. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Remove dentures if any. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. Never give anything by mouth to an unconscious person. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
- Skin contact** : Get medical attention immediately. Chemical burns must be treated promptly by a physician. Provide a readily-accessible eyewash facility and quick-drench safety shower. In case of contact, immediately flush skin with plenty of water for at least 30 minutes while removing contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Get medical attention immediately. Chemical burns must be treated promptly by a physician. Check for and remove any contact lenses. Immediately flush eyes with running water for at least 30 minutes, keeping eyelids open.

### Over-exposure signs/symptoms

See section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Personnel should wear protective clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Specific hazards arising from the chemical** : Oxidizing material. May intensify fire. In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
nitrogen oxides  
metal oxide/oxides
- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

*Continued on next page*

## Section 5. Fire-fighting measures

Remark : Not available.

## Section 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Do not absorb in sawdust or other combustible material. It may lead to a fire risk when it dries out. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). The spilled material may be neutralized with sodium carbonate, sodium bicarbonate or sodium hydroxide. Do not absorb in sawdust or other combustible material. It may lead to a fire risk when it dries out. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## Section 7. Handling and storage

**Precautions for safe handling** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Put on appropriate personal protective equipment (see section 8). Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Be sure area is equipped with all necessary emergency equipment including fire extinguishers, and spill response materials. Keep away from alkalis. Keep away from combustible materials. Empty containers retain product residue and can be hazardous. Do not reuse product container. Avoid breathing dust. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Avoid release to the environment. Do not breathe gas, fumes or vapor.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from alkalis. Separate from reducing agents and combustible materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Continued on next page

## Section 8. Exposure controls/personal protection

### Control parameters

Ingredient name	Exposure limits
Inorganic acid 1	ACGIH TLV (United States, 3/2012). STEL: 10 mg/m <sup>3</sup> 15 minute(s). STEL: 4 ppm 15 minute(s). TWA: 5.2 mg/m <sup>3</sup> 8 hour(s). TWA: 2 ppm 8 hour(s).
Chromium III Salt	ACGIH TLV (United States, 2/2006). TWA: 0.5 mg/m <sup>3</sup> 8 hour(s). Form: As Chromium ACGIH TLV (United States, 3/2012). Notes: measured as Cr TWA: 0.5 mg/m <sup>3</sup> , (measured as Cr) 8 hour(s). Form: Inorganic

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Avoid contact with eyes. Use safety eyewear designed to protect against splash of liquids.
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Avoid contact with skin and clothing. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

## Section 9. Physical and chemical properties

Physical state	: Liquid.
Color	: Green.
Odor	: Sharp Acidic.
Odor threshold	: Not available.
pH	: <1.5
Melting point	: Not available.
Boiling point	: 100°C (212°F)
Flash point	: Not available.
Burning time	: Not applicable.
Burning rate	: Not applicable.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.35
Solubility	: Easily soluble in the following materials: cold water and hot water.
Octanol/water partition coefficient	: Not available.
Decomposition temperature	: Not available.
Auto-ignition temperature	: Not available.
Viscosity	: Not available.

## Section 10. Stability and reactivity

Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Hazardous reactions or instability may occur under certain conditions of storage or use. Conditions may include the following: contact with combustible materials Reactions may include the following: risk of causing or intensifying fire
Conditions to avoid	: Drying on clothing or other combustible materials may cause fire. Avoid release to the environment.
Incompatibility with various substances	: Reactive with combustible materials, organic materials, alkalis.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Other Hazardous decomposition products	: Chromium Oxides, oxides of nitrogen and sulfur
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.

## Section 11. Toxicological information

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

### Potential health effects

- Inhalation** : Fatal if inhaled. May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. Adverse symptoms may include the following: respiratory tract irritation coughing
- Ingestion** : May cause burns to mouth, throat and stomach.
- Skin** : Causes severe burns.
- Eyes** : Causes serious eye damage. Direct contact with the eyes can cause irreversible damage, including blindness.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	9750 mg/kg
Inhalation (vapors)	0.195 mg/l

Product/ingredient name	Result	Species	Dose	Exposure
Inorganic acid 1	LC50 Inhalation Vapor	Rat	130 mg/m <sup>3</sup>	4 hours
	LDLo Oral	Human	430 mg/kg	-
Chromium III Salt	LD50 Oral	Rat	3250 mg/kg	-

Additional information:

## Section 12. Ecological information

Ecotoxicity : This material is very toxic to aquatic life.

### Aquatic and terrestrial toxicity

Product/ingredient name	Test	Result		
Inorganic acid 1	-	Acute LC50 180000 ug/L Marine water	Crustaceans - Green or European shore crab - Carcinus maenas - Adult	48 hours
Chromium III Salt	-	Acute IC50 47.7 ug/L Fresh water	Algae - Green algae - Pseudokirchneriella subcapitata	4 days
	-	Acute LC50 19270 ug/L Marine water	Crustaceans - Calanoid copepod - Acartia clausi - Adult	48 hours
	-	Acute LC50 9320 to 11380 ug/L Fresh water	Daphnia - Water flea - Daphnia magna	48 hours
	-	Acute LC50 4400 to 4612 ug/L Fresh water	Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling) - 37 mm - 0.69 g	96 hours

Conclusion/Summary : Not available.

Continued on next page

## Section 12. Ecological information

### Persistence/degradability

Product/ingredient name	Test	Result
Not available.		

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis
Not available.		

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Inorganic acid 1	-0.21	-	low






Mobility : Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG* Label	Additional information
DOT Classification	UN3093	CORROSIVE LIQUID, OXIDIZING, N.O.S. (Inorganic acid 1, Chromium III Salt)	8 (5.1)	II  	ERG#140 -
IMDG Class	UN3093	CORROSIVE LIQUID, OXIDIZING, N.O.S. (Inorganic acid 1, Chromium III Salt). Marine pollutant (Chromium III Salt)	8 (5.1)	II   	-

Continued on next page



## Section 14. Transport information

IATA-DGR Class	UN3093	CORROSIVE LIQUID, OXIDIZING, N.O.S. (Inorganic acid 1, Chromium III Salt)	8 (5.1)	II	  	-
UN Class	UN3093	CORROSIVE LIQUID, OXIDIZING, N.O.S. (Inorganic acid 1, Chromium III Salt)	8 (5.1)	II	  	-

PG\* : Packing group

## Section 15. Regulatory information

### China

#### List of Toxic Chemicals Severely Restricted for Importing & Exporting by China

None of the components are listed.

### Korea

#### a. Regulation according to ISHA

ISHA Article 37 : None of the components are listed.

ISHA Article 38 : None of the components are listed.

#### b. Regulation according to TCCA

TCCA Toxic chemicals : Toxic

TCCA Observational chemicals : None of the components are listed.

TCCA Article 32 (Banned) : None of the components are listed.

TCCA Article 32 (Restricted) : None of the components are listed.

#### c. Dangerous Materials Control Act : Not available.

### Europe

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

### Japan

#### Poisonous and Deleterious Substances

Ingredient name

Inorganic acid 1

Status

Deleterious

### ISHL

Continued on next page

## Section 15. Regulatory information

ISHL Class	: Class 3
Working Conditions Act; Health and Safety Act	: Corrosive.Clause 326.
ISHL Prevention of Tetraalkyl Lead Poisoning	: Not listed
ISHL Harmful Substances Subject to Obtaining Permission for Manufacturing	: Not listed
ISHL Harmful Substances, Prohibited for Manufacturing	: Not listed
ISHL Chemicals requiring notification	: Listed
ISHL Dangerous Substances	: Oxidizing
List of Specially Controlled Industrial Waste	: Not listed
<u>Pollutant Release and Transfer Registers (PRTR)</u>	: Class 1
<u>Fire Service Law - Obstructive materials</u>	: Not listed
<u>Taiwan</u>	
List of chemicals for which manufacturing or handling is defined as "work specially hazardous to health"	: This product contains substances "Specially hazardous to health": Inorganic acid 1.
List of chemicals reputed to be a "threat of imminent danger"	: This product contains substances considered to be a "Threat of imminent danger": Inorganic acid 1.
LSHL Article 21	: This product contains substances listed on "LSHL Article 21": Chromium III Salt.
<u>International lists</u>	
United States TSCA	: <b>TSCA 5(a)2 proposed significant new use rules:</b> No products were found. <b>TSCA 5(a)2 final significant new use rules:</b> No products were found. <b>TSCA 12(b) one-time export:</b> No products were found. <b>TSCA 12(b) annual export notification:</b> No products were found.
United States inventory (TSCA 8b)	: All components are listed or exempted.

## Section 16. Other information

### History

Validation date	: 1/23/2014.
Supersedes Date	: 3/27/2013.
Prepared by	: T. Valverde (203)-799-4940

Continued on next page

## **Section 16. Other information**

Enthone Inc  
350 Frontage Road  
West Haven, CT 06516  
Phone: (203) 934-8611  
Fax: (203) 799-8179  
www.enthone.com

### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

4.1b1161



**enthone**®  
an Alent plc Company